

200H - Riveting engineers hammers




Standards:

NF E 71-016, NF ISO 15601, ISO 15601

Description:

- High safety hickory handle, triple fit: 2 steel wedges and 1 wood wedge.

	Length L [mm]	Length L1 [mm]	Length L2 [mm]	Handle ["]	Weight [g]
200H.26	245.0	80.0	25.0	210.MHB01	345.0
200H.28	270.0	88.0	28.0	210.MHB02	380.0
200H.30	270.0	93.0	30.0	210.MHB03	470.0
200H.30PB	270.0	93.0	30.0	210.MHB03	470.0
200H.32	300.0	100.0	32.0	210.MHB04	585.0
200H.32PB	300.0	100.0	32.0	210.MHB04	585.0
200H.36	300.0	106.0	35.0	210.MHB04	725.0
200H.36PB	300.0	106.0	35.0	210.MHB04	725.0
200H.40	330.0	108.0	40.0	210.MHB05	1000.0
200H.40PB	330.0	108.0	40.0	210.MHB05	1000.0
200H.42	330.0	117.0	42.0	210.MHB05	1100.0
200H.50	360.0	138.0	50.0	210.MHB06	1900.0
200H.50PB	360.0	138.0	50.0	210.MHB06	1900.0
200H.60	380.0	151.0	60.0	210.MHB27	2800.0