## 440.1P1/8SLS | 440.SLS - Inch combination wrenches



## Standards: ASME B107.100, SAE AS954G Description:

• Tool equipped with a FACOM SLS attachment solution, preventing any risk of accidental falls.

• The crimped "sliding" cable solution, selected and tested by FACOM, maintains user ergonomics (8 - 30 mm wrenches).

• Standard wrench for all current applications.

• High mechanical strength combined with compact size meeting aeronautical standards.

• Ring head: - Ring open end (size E) designed for better access to series or embedded screws. - OGV® profile with 12-point ring for powerful tightening while protecting the nut. - Ring head angled at 15°.

• Open end head: - Open end angled at 15°. - Open end head-handle geometry optimised for increased access.

- Dimensions in inches: from 1/4" to 1"5/16.
- Presentation: satin chrome finish.

## 440.1P1/8SLS



| A [in]             | 1`1/8 |
|--------------------|-------|
| Length L [mm]      | 305.0 |
| Thickness E [mm]   | 10.6  |
| Thickness E1 [mm]  | 16.1  |
| Thickness E2 [mm]  | 10.7  |
| Head Width B [mm]  | 60.7  |
| Head Width B1 [mm] | 40,6  |
| Weight [Kg]        | 0,44  |