

## SLS.G64 | SLS.G - Heat Shrink Sheath with metal "D" ring



### Description:

- Shrink tubing fitted with a strap and a metal "D" ring - SLS. This solution allows you to add an attachment point to all types of products and make them compatible with lanyards and carabiners from the facom sls range. Examples: special tools, pens, sprays etc. The strap surrounds the shrink tubing for strength and maximum security for all.
- Fabric resistant to common solvents.
- Sheath equipped with an adhesive which becomes liquid with the heat during the retraction of the sheath. optimum temperature of withdrawal: between 150 and 300 ° depending on the thickness and diameter of the sheath. Excellent adhesion on most substrates: crude steel, chrome or phosphate, aluminum, wood, plastic, ... Precautions: - Clean and degrease the product that will receive the shrink tubing. - Select the correct diameter of shrink-hose according to the allocation table. - Identify a location where the sheath will not harm ergonomics. If possible, choose a location where the sheath can not escape once retracted. - Respect the maximum weight recommended. - Heat the sheath about 3cm away with a standard heat gun Facom E.2015. Be careful not to burn the strap. - Allow to cool for 5 minutes to obtain optimum adhesion of the glue. - Check the bond. - Check the equipment

periodically.

 <b>SLS.G64</b>	
Diameter [mm]	70.0
Diameter D Mini - Maxi [mm]	38 - 64
Length L1 [mm]	88.0
Length L2 [mm]	16.0
Height H [mm]	50.0
Weight [g]	55.0