

**U.306-170N U.306N - Inside pullers****Description:**

- Versatile: takes 2 or 3 legs. Converts into outside puller with the legs U.306G1 + screw U.306-4 or legs U.306G10 + screw U.306-2 or legs U.306G15 + screw U.306-3 (supplied fitted with its extension).
- Comfort: self-gripping legs by return spring. The puller stays in rolling position even when not in tension.
- Safety: legs locked in position on the bearing using a knob. No risk for the puller to escape from the bearing.
- Shear pin: the pin shears if torque limit is exceeded. Supplied with 2 spare pins.
- Set of 3 spare pins. Refer to spares table according to puller power.
- Adaptable puller accessories: slide hammer U.306M (direct attachment) and beam U.40 (attached using ring and nut U.306A1 to be ordered separately).

<b>C mini - maxi [mm]:</b>	50 - 170
----------------------------	----------

<b>L x l x H [mm]:</b>	135 x 285 x 320
------------------------	-----------------

<b>P maxi [mm]:</b>	190
---------------------	-----

<b>Hex Size [mm]:</b>	18
-----------------------	----

<b>Legs:</b>	U.306G20
--------------	----------

<b>Ton [t]:</b>	4
-----------------	---

<b>Screw Size:</b>	U.306-2
--------------------	---------

<b>Screw Size [mm]:</b>	18
-------------------------	----

<b>T [kN]:</b>	40
----------------	----

<b>[kg]:</b>	1,800
--------------	-------

